



TECHNICAL SPECIFICATIONS



EKO FORZA PLUS SAE 15W-40 Commercial vehicle engine oil

DESCRIPTION

EKO FORZA PLUS 15W-40 is a high quality, heavy duty diesel engine oil, suitable for heavy duty vehicles and for off-road equipment operating in constructions, agriculture and mining. EKO FORZA PLUS 15W-40 is suitable for both modern engines and older models.

SPECIFICATIONS

ACEA E5, API CH-4/SJ, MB 228.1, MAN M 3275-1, VOLVO VDS-2

OEM Approvals

MTU Type 2 approval

APPLICATIONS

EKO FORZA PLUS 15W-40 is suitable for both naturally aspirated and turbo-charged engines operating in a wide range of on- and off-highway applications and in various conditions and environments.

EKO FORZA PLUS 15W-40 meets ACEA E5 and API CH-4 quality level, holds MTU Type 2 approval and meets demanding specifications of major OEMs like VOLVO, MERCEDES BENZ and MAN. As a result of this, it is a reliable and cost effective choice for the lubrication of almost all of the heavy duty vehicles found in mixed fleets of various manufacturers and ages.

BENEFITS

- Excellent anti-wear and corrosion protection, which promotes longer engine life and reduced maintenance and service costs.
- Superior oxidation and thermal stability, which reduces deposits and sludge build-up and prevents viscosity increase, thus promoting extended oil and engine life.
- High shear stability, which maintains a strong lubricating film at high temperatures.
- Very good low temperature viscosity characteristics, which enable easy start-up and reduce wear.

The information provided from this data sheet is accurate as of the date printing. For more information/ clarifications, please contact EKO ABEE Technical Support,
Tel. + 30 210 5509 511, +30 210 7725 418.

For recommendations on safe handling and use of this product, please refer to Safety Data Sheet.



TECHNICAL SPECIFICATIONS



EKO FORZA PLUS SAE 15W-40 Commercial vehicle engine oil

TYPICAL PROPERTIES

Properties	Methods	Units	EKO FORZA PLUS SAE 15W-40
SAE Classification	-	-	15W-40
Viscosity @100°C	ASTM D 445	cSt	13,69
Viscosity @40°C	ASTM D 445	cSt	100,3
Viscosity Index (VI)	ASTM D 2270	-	137
Sulfated Ash	ASTM D 874	% w/w	1,1
Density @ 15°C	ASTM D 4052	g/ml	0,884
TBN	ASTM D2896	mg KOH/g	8,9
Pour Point	ASTM D 5950	°C	-30
Flash Point	ASTM D 92	°C	240

HYGIENE AND SAFETY

Used lubricants must be collected in an authorized collection area. They must not be mixed with solvents, water, brake fluids and antifreeze. Do not dispose into drains, soil or water.

The information provided from this data sheet is accurate as of the date printing. For more information/ clarifications, please contact EKO ABEE Technical Support,
Tel. + 30 210 5509 511, +30 210 7725 418.

For recommendations on safe handling and use of this product, please refer to Safety Data Sheet.