



TECHNICAL SPECIFICATIONS



EKO GEOTRON SAE 20W-50 Vehicle and general purpose lubricant

DESCRIPTION-APPLICATIONS

EKO GEOTRON 20W-50 is a mineral engine lubricant which is developed for use in older technology, gasoline and diesel passenger cars and vans.

EKO GEOTRON 20W-50 provides sufficient protection and lubrication over a wide temperature range. It is particularly recommended for engines with many miles of operation.

EKO GEOTRON 20W-50 is a multi-purpose lubricant, so it is suitable for many other applications, where an engine oil of API SF or API CF quality level is recommended.

SPECIFICATIONS

API SF/CF

BENEFITS

- Good performance and protection under normal operating conditions / oil-drain intervals.
- Good oxidation and thermal stability, which reduces deposits and helps keep engine clean.
- The SAE 20W50 viscosity grade provides perfect performance in warm atmospheres.

The information provided from this data sheet is accurate as of the date printing. For more information/ clarifications, please contact EKO ABEE Technical Support,
Tel. + 30 210 5509 511, +30 210 7725 418.
For recommendations on safe handling and use of this product, please refer to Safety Data Sheet.



TECHNICAL SPECIFICATIONS



EKO GEOTRON SAE 20W-50 Vehicle and general purpose lubricant

TYPICAL PROPERTIES

Properties	Methods	Units	EKO GEOTRON SAE 20W-50
SAE Classification	-	-	20W-50
Viscosity @100°C	ASTM D 445	cSt	17,8
Viscosity @40°C	ASTM D 445	cSt	153,4
Viscosity Index (VI)	ASTM D 2270	-	128
Density @ 15°C	ASTM D 4052	g/ml	0,890
Sulfated Ash	ASTM D 874	% w/w	0,9
Total Base Number (TBN)	ASTM D2896	mg KOH/g	6,5
Pour Point	ASTM D 5950	°C	-24
Flash Point	ASTM D 92	°C	220

HYGIENE AND SAFETY

Used lubricants must be collected in an authorized collection area. They must not be mixed with solvents, water, brake fluids and antifreeze. Do not dispose into drains, soil or water.

The information provided from this data sheet is accurate as of the date printing. For more information/ clarifications, please contact EKO ABEE Technical Support,
Tel. + 30 210 5509 511, +30 210 7725 418.
For recommendations on safe handling and use of this product, please refer to Safety Data Sheet.