



TECHNICAL SPECIFICATIONS



EKO MEGATRON SUPER SAE 15W-40

Passenger vehicle engine oil

DESCRIPTION

EKO MEGATRON SUPER 15W-40 is a high quality engine oil suitable for passenger car gasoline and diesel engines and for light truck diesel engines, where manufacturer recommends a SAE 15W-40 grade lubricant of API SL/CF or ACEA A3/B3 or earlier specifications.

It is also suitable for the lubrication of LPG / CNG engines and for gasoline engines using LPG as an alternative fuel.

SPECIFICATIONS

ACEA A3/B3, API SL/CF, MB 229.1

APPLICATIONS

EKO MEGATRON SUPER SAE 15W-40 is suitable for use in passenger cars, light trucks, SUVs and vans, always in accordance with manufacturers' recommendations.

BENEFITS

- Provides sufficient engine cleanliness and effective wear protection.
- Maintains film strength under extreme temperature conditions.
- Provides continuous protection in normal oil service conditions.

The information provided from this data sheet is accurate as of the date printing. For more information/ clarifications, please contact EKO ABEE Technical Support,
Tel. + 30 210 5509 511, +30 210 7725 418.
For recommendations on safe handling and use of this product, please refer to Safety Data Sheet.



TECHNICAL SPECIFICATIONS



EKO MEGATRON SUPER SAE 15W-40 Passenger vehicle engine oil

TYPICAL PROPERTIES

Properties	Methods	Units	EKO MEGATRON SUPER SAE 15W-40
SAE Classification	-	-	15W-40
Viscosity @100°C	ASTM D 445	cSt	13,9
Viscosity @40°C	ASTM D 445	cSt	101,9
Viscosity Index (VI)	ASTM D 2270	-	138
Sulfated Ash	ASTM D 874	% w/w	1,1
Density @ 15°C	ASTM D 4052	g/ml	0,882
Pour Point	ASTM D 5950	°C	-30
Flash Point	ASTM D 92	°C	220

HYGIENE AND SAFETY

Used lubricants must be collected in an authorized collection area. They must not be mixed with solvents, water, brake fluids and antifreeze. Do not dispose into drains, soil or water.

The information provided from this data sheet is accurate as of the date printing. For more information/ clarifications, please contact EKO ABEE Technical Support,
Tel. + 30 210 5509 511, +30 210 7725 418.
For recommendations on safe handling and use of this product, please refer to Safety Data Sheet.