



TECHNICAL SPECIFICATIONS



EKO MEGATRON ULTRA DIESEL 10W-40

Passenger vehicle engine oil

DESCRIPTION

EKO MEGATRON ULTRA DIESEL 10W-40 is a premium performance semi-synthetic engine oil, suitable for all modern, high performance passenger car and light truck diesel engines, where manufacturer recommends a SAE 10W-40 engine oil meeting ACEA A3/B4, API SL/CF or earlier specifications.

SPECIFICATIONS

ACEA A3/B3/B4, API SL/CF, MB 229.1, VW 501 01/505 00.

APPLICATIONS

Suitable for all type of diesel vehicles, where manufacturer suggests ACEA A3/B4, ACEA A3/B3 or API SL/CF quality level.

BENEFITS

- Offers maximum engine cleanliness and protection at all operating temperatures.
- Reduces deposits and sludge build-up, maintaining maximum engine cleanliness and enabling extended oil life.
- Provides excellent low and high temperature performance.
- Maintains film strength even under the most difficult driving conditions.

The information provided from this data sheet is accurate as of the date printing. For more information/ clarifications, please contact EKO ABEE Technical Support,
Tel. + 30 210 5509 511, +30 210 7725 418.
For recommendations on safe handling and use of this product, please refer to Safety Data Sheet.



TECHNICAL SPECIFICATIONS



EKO MEGATRON ULTRA DIESEL 10W-40 Passenger vehicle engine oil

TYPICAL PROPERTIES

Properties	Methods	Units	EKO MEGATRON ULTRA DIESEL SAE 10W-40
SAE Classification	-	-	10W-40
Viscosity @100°C	ASTM D 445	cSt	13,65
Viscosity @40°C	ASTM D 445	cSt	90,83
Viscosity Index (VI)	ASTM D 2270	-	153
Sulfated Ash	ASTM D 874	% w/w	1,25
Density @ 15°C	ASTM D 4052	g/ml	0,874
Pour Point	ASTM D 5950	°C	-36
Flash Point	ASTM D 92	°C	228

HYGIENE AND SAFETY

Used lubricants must be collected in an authorized collection area. They must not be mixed with solvents, water, brake fluids and antifreeze. Do not dispose into drains, soil or water.

The information provided from this data sheet is accurate as of the date printing. For more information/ clarifications, please contact EKO ABEE Technical Support,
Tel. + 30 210 5509 511, +30 210 7725 418.
For recommendations on safe handling and use of this product, please refer to Safety Data Sheet.