



TECHNICAL SPECIFICATIONS



EKO GEAROL RPC SAE 75W-80 Premium automotive gear oil

DESCRIPTION-APPLICATIONS

EKO GEAROL RPC 75W-80 is a premium performance, extreme pressure (EP) multigrade gear oil specially designed for manual transmissions of Peugeot, Citroen and Rover cars.

It is also suitable for all manual transmissions requiring an API GL-4, SAE 75W-80 gear oil.

EKO GEAROL RPC 75W-80 provides effective transmission under the most severe operating conditions.

SPECIFICATIONS

API GL-4

BENEFITS

- Superior low temperature fluidity, which ensures easy start up and excellent performance at low ambient temperatures.
- High shear stability provides a strong lubricating film at high temperatures.
- Exceptional thermal and oxidation stability prevents deposits build up and offers extended lifetime and smooth operation of the transmission.
- Excellent protection from deposits and formation of lacquers increases extended drain and service interval potential.

The information provided from this data sheet is accurate as of the date printing. For more information/ clarifications, please contact EKO ABEE Technical Support,
Tel. + 30 210 5509 511, +30 210 7725 418.
For recommendations on safe handling and use of this product, please refer to Safety Data Sheet.



TECHNICAL SPECIFICATIONS



EKO GEAROL RPC SAE 75W-80 Premium automotive gear oil

TYPICAL PROPERTIES

Properties	Methods	Units	EKO GEAROL RPC SAE 75W-80
SAE Classification	-	-	75W-80
Viscosity @100°C	ASTM D 445	cSt	8,97
Viscosity @40°C	ASTM D 445	cSt	50,0
Viscosity Index (VI)	ASTM D 2270	-	161
Density @ 15°C	ASTM D 4052	g/ml	0,878
Brookfield Viscosity at -40°C	ASTM D2983	cP	30.000
Pour Point	ASTM D 5950	°C	-48
Flash Point	ASTM D	°C	214

HYGIENE AND SAFETY

Used lubricants must be collected in an authorized collection area. They must not be mixed with solvents, water, brake fluids and antifreeze. Do not dispose into drains, soil or water.

The information provided from this data sheet is accurate as of the date printing. For more information/ clarifications, please contact EKO ABEE Technical Support,
Tel. + 30 210 5509 511, +30 210 7725 418.
For recommendations on safe handling and use of this product, please refer to Safety Data Sheet.