



## TECHNICAL SPECIFICATIONS



### EKO MEGATRON PLATINUM FORMULA C SAE 5W-30 Passenger vehicle engine oil

#### DESCRIPTION-APPLICATIONS

EKO MEGATRON PLATINUM FORMULA C 5W-30 is an advanced technology, fully synthetic engine oil developed for modern, high performance and low-emission gasoline and diesel engines.

EKO MEGATRON PLATINUM FORMULA C 5W-30 is suitable for almost all modern engines of European and Asian manufacturers including VOLKSWAGEN, MERCEDES BENZ, GENERAL MOTORS, BMW, FIAT, TOYOTA, PSA, KIA and HYUNDAI.

It is the right choice for engines where manufacturer recommends either ACEA C3 or ACEA C2 quality level and SAE 5W-30 viscosity grade, and for vehicles equipped with modern exhaust after-treatment systems including diesel particulate filters (DPFs).

EKO MEGATRON PLATINUM FORMULA C 5W-30 is suitable for use in LPG/CNG engines and in gasoline engines using LPG as an alternative fuel.

#### SPECIFICATIONS

ACEA C3, ACEA C2, API SN, VW 502 00/505 01, VW 502 00/505 00, MB 229.31/229.51, BMW LL-04, GM dexos 2, PSA B71 2290.

#### BENEFITS

- Its special formulation guarantees superior engine cleanliness which increases engine life.
- Provides maximum engine performance even under the most severe driving conditions.
- The specially selected mid-SAPS additive system increases the lifetime of catalytic exhaust after treatment devices and improves vehicle fuel economy.
- EKO MEGATRON PLATINUM FORMULA C 5W-30 is developed to provide a lubricating film of high strength and protection, thus enabling extended oil drain and service intervals.

The information provided from this data sheet is accurate as of the date printing. For more information/ clarifications, please contact EKO ABEE Technical Support,  
Tel. + 30 210 5509 511, +30 210 7725 418.  
For recommendations on safe handling and use of this product, please refer to Safety Data Sheet.



## TECHNICAL SPECIFICATIONS



### EKO MEGATRON PLATINUM FORMULA C SAE 5W-30 Passenger vehicle engine oil

#### TYPICAL PROPERTIES

Properties	Methods	Units	EKO MEGATRON PLATINUM FORMULA C SAE 5W-30
SAE Classification	-	-	5W-30
Viscosity @100°C	ASTM D 445	cSt	12,3
Viscosity @40°C	ASTM D 445	cSt	74,5
Viscosity Index (VI)	ASTM D 2270	-	164
Sulfated Ash	ASTM D 874	% w/w	0,7
Density @ 15°C	ASTM D 4052	g/ml	0,858
Pour Point	ASTM D 5950	°C	-45
Flash Point	ASTM D 92	°C	232

#### HYGIENE AND SAFETY

Used lubricants must be collected in an authorized collection area. They must not be mixed with solvents, water, brake fluids and antifreeze. Do not dispose into drains, soil or water.

The information provided from this data sheet is accurate as of the date printing. For more information/ clarifications, please contact EKO ABEE Technical Support,  
Tel. + 30 210 5509 511, +30 210 7725 418.  
For recommendations on safe handling and use of this product, please refer to Safety Data Sheet.