



## TECHNICAL SPECIFICATIONS



### EKO MEGATRON PLATINUM FORMULA V SAE 5W-30 Passenger vehicle engine oil

#### DESCRIPTION-APPLICATIONS

EKO MEGATRON PLATINUM FORMULA V 5W-30 is a top tier, fully synthetic engine oil developed for modern, high performance gasoline and diesel engines.

EKO MEGATRON PLATINUM FORMULA V 5W-30 is specially developed for VOLKSWAGEN group engines (VW, Audi, Skoda, Seat) requiring a VW 504 00 or VW 507 00 engine oil, but is also suitable for earlier VW engines requiring VW 503 00 and VW 503 01 specifications.

It is the right choice for diesel passenger cars and light duty vehicles equipped with diesel particulate filters (DPFs), and for gasoline and diesel vehicles, where manufacturer recommends an ACEA C3 engine oil of SAE 5W-30 viscosity grade.

EKO MEGATRON PLATINUM FORMULA V 5W-30 is suitable for LPG / CNG engines and for gasoline engines using LPG as an alternative fuel.

#### SPECIFICATIONS

ACEA C3, VW 504 00/507 00, MB 229.31/229.51, BMW LongLife-04, Porsche C30.

#### BENEFITS

- Special formulation developed to meet the needs of the injection systems of the VW group engines.
- It is specially engineered to provide very flexible oil drain intervals and fuel economy.
- Thanks to its low sulfur, sulfated ash and phosphorus content, EKO MEGATRON PLATINUM FORMULA V 5W-30 protects effectively the modern catalytic exhaust after treatment systems and contributes to emissions reduction.
- By addressing effectively the three major causes of engine stress that is high temperature, deposits and wear, offers unique levels of protection, cleanliness and performance.

The information provided from this data sheet is accurate as of the date printing. For more information/ clarifications, please contact EKO ABEE Technical Support,  
Tel. + 30 210 5509 511, +30 210 7725 418.  
For recommendations on safe handling and use of this product, please refer to Safety Data Sheet.



## TECHNICAL SPECIFICATIONS



### EKO MEGATRON PLATINUM FORMULA V SAE 5W-30 Passenger vehicle engine oil

#### TYPICAL PROPERTIES

Properties	Methods	Units	EKO MEGATRON PLATINUM FORMULA V SAE 5W-30
SAE Classification	-	-	5W-30
Viscosity @100°C	ASTM D 445	cSt	12,1
Viscosity @40°C	ASTM D 445	cSt	70,5
Viscosity Index (VI)	ASTM D 2270	-	170
Sulfated Ash	ASTM D 874	% w/w	0,76
Density @ 15°C	ASTM D 4052	g/ml	0,853
Pour Point	ASTM D 5950	°C	-39
Flash Point	ASTM D 92	°C	238

#### HYGIENE AND SAFETY

Used lubricants must be collected in an authorized collection area. They must not be mixed with solvents, water, brake fluids and antifreeze. Do not dispose into drains, soil or water.

The information provided from this data sheet is accurate as of the date printing. For more information/ clarifications, please contact EKO ABEE Technical Support,  
Tel. + 30 210 5509 511, +30 210 7725 418.  
For recommendations on safe handling and use of this product, please refer to Safety Data Sheet.