



TECHNICAL SPECIFICATIONS



EKO MOTO SYNTHETIC 4T SAE 5W-40 Fully synthetic engine oil for 4-stroke Motorcycles

DESCRIPTION

EKO MOTO SYNTHETIC 4T 5W-40 is a fully synthetic engine oil, specially designed for latest technology and high performance 4-stroke motorcycle engines. Offers excellent protection to engines and gearboxes, superior clutch performance and outstanding performance in both on- and off-road driving.

SPECIFICATIONS

API SL, JASO MA2

APPLICATIONS

EKO MOTO SYNTHETIC 4T 5W-40 is suitable for all 4-stroke motorcycles, where manufacturer recommends an engine oil of SAE 5W-40, API SL and JASO MA2 quality level.

EKO MOTO SYNTHETIC 4T 5W-40 is the first choice for scooters of all leading European and Japanese manufacturers.

BENEFITS

- Suitable for both urban-with stops and starts-and interurban operating conditions.
- Excellent viscosity characteristics, which enable easy start-up at low ambient temperatures and provide strong lubricating film at high temperatures.
- Superior engine protection and maximum performance in a wide range of temperatures and in various driving conditions.

The information provided from this data sheet is accurate as of the date printing. For more information/ clarifications, please contact EKO ABEE Technical Support,
Tel. + 30 210 5509 511, +30 210 7725 418.
For recommendations on safe handling and use of this product, please refer to Safety Data Sheet.



TECHNICAL SPECIFICATIONS



EKO MOTO SYNTHETIC 4T SAE 5W-40

Fully synthetic engine oil for 4-stroke Motorcycles

TYPICAL PROPERTIES

Properties	Methods	Units	EKO MOTO SYNTHETIC 4T SAE 5W-40
SAE Classification	-	-	5W-40
Viscosity @100°C	ASTM D 445	cSt	14,2
Viscosity @40°C	ASTM D 445	cSt	87,2
Viscosity Index (VI)	ASTM D 2270	-	168
Density @ 15°C	ASTM D 4052	g/ml	0,856
Sulfated Ash	ASTM D 874	% w/w	1,1
TBN	ASTM D2896	mg KOH/g	7,9
Pour Point	ASTM D 5950	°C	-33
Flash Point	ASTM D 92	°C	236

HYGIENE AND SAFETY

Used lubricants must be collected in an authorized collection area. They must not be mixed with solvents, water, brake fluids and antifreeze. Do not dispose into drains, soil or water.

The information provided from this data sheet is accurate as of the date printing. For more information/ clarifications, please contact EKO ABEE Technical Support,
Tel. + 30 210 5509 511, +30 210 7725 418.
For recommendations on safe handling and use of this product, please refer to Safety Data Sheet.